



MASSEY FERGUSON



# MF 2600 H SERIES

45-75 HP

A MODERN CLASSIC



# MF 2600 H SERIES

**A MODERN CLASSIC**

175 YEARS AGO, WE PIONEERED THE EQUIPMENT THAT WOULD ULTIMATELY BECOME THE FAMED MASSEY FERGUSON® TRACTOR. AND NOW, ALL OVER THE WORLD, THERE ARE MORE MASSEY FERGUSON TRACTORS ON THE JOB THAN ANY OTHER BRAND.



## 4 A HARDWORKING TRACTOR



## 5 STRAIGHTFORWARD VALUE



## 6 PARTS & SERVICE



## 7 TECHNICAL SPECIFICATIONS

|                               |   |
|-------------------------------|---|
| A Hardworking Tractor .....   | 4 |
| Straightforward Value .....   | 5 |
| Parts & Service .....         | 6 |
| Technical Specifications..... | 7 |



#### RUBBER FLOOR MATS

- ▶ Allows for a more comfortable ride with decreased vibration.

#### 2WD AND 4WD FRONT AXLE OPTIONS

- ▶ Offered in both two- and four-wheel drive, you have cost flexibility and application versatility for whatever work you need to get done.

#### DEBRIS/HEAT SHIELDS

- ▶ Located on the floor near the operator's feet, the debris shields provide a cooler and cleaner drive.

#### OPERATOR STATION

- ▶ The simple, open-platform design makes entering and exiting the tractor easy, while the ReverseRise seat offers more leg room and great visibility.

#### DURABILITY

- ▶ Steel hood, fenders and platform mean this tractor is in it for the long haul, even in tough conditions.

#### HYDRAULICS

- ▶ The high-capacity hydraulics make loader and implement work simple.

#### LOADER

- ▶ Attaching and changing the bucket is easy with skid-steer style coupling.

#### EASY FUEL FILL

- ▶ Ground-level fuel tank provides easy access.

# STRAIGHTFORWARD **VALUE.**

# PARTS & SERVICE

## IT'S ALL ABOUT A LIFETIME OF SUPPORT

Buying, owning and maintaining equipment can be complex. That's why ensuring you have support and peace of mind is always an important consideration. With Massey Ferguson, you can count on personalized, responsive support from our network of dealers. Plus, there's no cut-off time for parts and service, meaning we're available to you throughout the lifetime of your machine.

There's a pride and responsibility built into every piece of equipment we sell, and we make it our mission to keep your machine running smoothly, every single time you turn the key.

Ask your dealer about AGCO Protection, an extended warranty program that prolongs your coverage and safeguards against the cost of sudden breakdowns.

AGCO replacement parts are made to the same high standards as those used on the assembly line, so your AGCO® equipment will stay running like new. Talk to your dealer, or shop at [parts.agcocorp.com](https://parts.agcocorp.com) to find the AGCO Genuine Parts you need.

Focus on your operation, not on scheduling maintenance. With AGCO GenuineCare plans, your service intervals are predetermined. You'll avoid downtime and be able to better plan your costs thanks to transparent pricing, bundles and discounts.



# TECHNICAL SPECIFICATIONS

| MODELS        |                                    | 2604 H                                                                                            |                                                          | 2605 H                                     |                                            | 2606 H                                     |  | 2607 H |  |
|---------------|------------------------------------|---------------------------------------------------------------------------------------------------|----------------------------------------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|--|--------|--|
| Engine        |                                    |                                                                                                   |                                                          |                                            |                                            |                                            |  |        |  |
|               | Rated engine power                 | HP (kW)                                                                                           | 45 (33.6)                                                | 55 (41.0)                                  | 65 (48.8)                                  | 74 (55.1)                                  |  |        |  |
|               | Rated engine speed                 | rpm                                                                                               | 2,000                                                    |                                            |                                            |                                            |  |        |  |
|               | Rated PTO power                    | HP (kW)                                                                                           | 38 (30.1)                                                | 46 (33.8)                                  | 55 (40.4)                                  | 64 (47)                                    |  |        |  |
|               | Engine                             | Simpson 2.6 L, 3-cylinder, Tier 4 final-compliant                                                 |                                                          |                                            |                                            |                                            |  |        |  |
|               | Air and fuel systems               | Intercooler turbo-charged with electronically controlled high-pressure common rail fuel injection |                                                          |                                            |                                            |                                            |  |        |  |
|               | Emission control                   | External cooled exhaust gas recirculation (EGR) with diesel oxidation catalyst (DOC)              |                                                          |                                            |                                            |                                            |  |        |  |
| Drivetrain    |                                    |                                                                                                   |                                                          |                                            |                                            |                                            |  |        |  |
|               | Mechanical transmission            | 8F x 2R SideShift                                                                                 | 2WD — 8F x 2R SideShift<br>4WD — 8F x 8R Synchro Shuttle |                                            | 8F x 8R Synchro Shuttle                    |                                            |  |        |  |
|               | Main clutch                        | Dual dry                                                                                          | Split torque clutch                                      |                                            |                                            |                                            |  |        |  |
|               | Rear axle                          | Direct drive                                                                                      |                                                          |                                            |                                            | Outboard planetary                         |  |        |  |
|               | Brakes                             | Drum brakes                                                                                       | Oil-immersed wet disc                                    |                                            |                                            |                                            |  |        |  |
|               | Differential lock                  | Mechanical engagement via right-side heel pedal                                                   |                                                          |                                            |                                            |                                            |  |        |  |
|               | Front axle                         | 2WD straight adjustable / 4WD planetary reduction                                                 |                                                          |                                            |                                            |                                            |  |        |  |
|               | 4WD engagement                     | Mechanical via push-pull lever in platform to left of seat                                        |                                                          |                                            |                                            |                                            |  |        |  |
| Hydraulics    |                                    |                                                                                                   |                                                          |                                            |                                            |                                            |  |        |  |
|               | Hydraulic system                   | Massey Ferguson hydraulics, Mark 1A scotch yoke piston pump                                       |                                                          |                                            |                                            |                                            |  |        |  |
|               | Hydraulic flow @ remote            | GPM (LPM)                                                                                         | 10.6 (40.1)                                              |                                            |                                            |                                            |  |        |  |
|               | Total hydraulic flow               | GPM (LPM)                                                                                         | 15.7 (59.5)                                              |                                            |                                            |                                            |  |        |  |
|               | Remote valves                      | One standard, two optional                                                                        |                                                          |                                            |                                            | Two standard                               |  |        |  |
|               | 3-point lift capacity @ pins       | lbs. (kg)                                                                                         | 3,747 (1,700)                                            | 4,519 (2,050)                              |                                            |                                            |  |        |  |
|               | 3-point lift capacity @ 24" behind | lbs. (kg)                                                                                         | 2,204 (1,000)                                            | 2,755 (1,250)                              |                                            |                                            |  |        |  |
|               | Rear PTO                           | 2WD & 4WD — live                                                                                  | 2WD — live<br>4WD — independent                          |                                            | 2WD & 4WD — independent                    |                                            |  |        |  |
| Operator Area |                                    |                                                                                                   |                                                          |                                            |                                            |                                            |  |        |  |
|               | Platform features                  | Debris/heat shield, rubber floormat                                                               |                                                          |                                            |                                            |                                            |  |        |  |
|               | Seat and steering                  | ReverseRise adjustable seat w/ fixed steering column                                              |                                                          |                                            |                                            |                                            |  |        |  |
| Dimensions    |                                    |                                                                                                   |                                                          |                                            |                                            |                                            |  |        |  |
|               | Overall length                     | in. (mm)                                                                                          | 2WD — 138 (3,510); 4WD — 139 (3,526)                     |                                            |                                            |                                            |  |        |  |
|               | Wheelbase                          | in. (mm)                                                                                          | 2WD — 80.7 (2,070); 4WD — 81.5 (2,050)                   |                                            |                                            |                                            |  |        |  |
|               | Overall width                      | in. (mm)                                                                                          | 64.6 (1,641)                                             | 66.5 (1,689)                               | 69.9 (1,775)                               | 72.9 (1,851)                               |  |        |  |
|               | Overall height                     | in. (mm)                                                                                          | 90.6 (2,300)                                             | 91.3 (2,320)                               | 93.9 (2,385)                               | 94.5 (2,400)                               |  |        |  |
|               | ROPS base weight without ballast   | lbs. (kg)                                                                                         | 2WD — 4,597 (2,085)<br>4WD — 4,927 (2,235)               | 2WD — 4,894 (2,220)<br>4WD — 5,394 (2,446) | 2WD — 5,115 (2,320)<br>4WD — 5,710 (2,590) | 2WD — 5,269 (2,390)<br>4WD — 5,864 (2,660) |  |        |  |
|               | Fuel capacity                      | gal. (L)                                                                                          | 14.5 (55)                                                |                                            |                                            |                                            |  |        |  |



**APPLY  
ONLINE**  
FOR FINANCING



APPLY NOW FOR PRE-APPROVAL\*  
[www.masseyferguson.us](http://www.masseyferguson.us)



or scan the QR code to get started.



\*Currently only available for individual applicants. Subject to credit review and approval and other terms and conditions. All financing is in AGCO Finance LLC's sole discretion.  
©2022 AGCO Corporation. Massey Ferguson is a worldwide brand of AGCO Corporation.  
AGCO and Massey Ferguson are trademarks of AGCO. All rights reserved. | MF22B006FCv02



**MASSEY FERGUSON**

BORN TO **FARM**

